

Model : BC-IPB20

## IP Camera Sony 2.0 MP/1080P

POE 10/100Mbps Ethernet internal

Starlight



มีไมโครโฟนในตัว

Main features:

- 1/2.8" low-light CMOS sensor;
- Independent two channels with 25fps ;
- H.264/H.265/H.265+ video compression standard,
- Support intelligent analysis
- Accurate human detection,
- Support zone detection;
- Support WDR, backlight compensation, glare suppression, DNR and image flip;
- Resolution up to 2304\*1296,Color 0.01 Lux@F1.2: supports standard ONVIF protocol
- Support ICR switching
- IP66 Metal Bullet casing
- 2PCS Array IR Led, 20M
- 2.8mm lens
- Power supply:PoE and DC12V 500mA
- Built-in Mic



### Specification

|                       |                                                                                                                                                                                                                                                                                              |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model                 | BC-IPB20                                                                                                                                                                                                                                                                                     |
| Sender                | 1/2.8", MP CMOS IMX307,low light                                                                                                                                                                                                                                                             |
| Minimum illumination  | Color 0.01 Lux                                                                                                                                                                                                                                                                               |
| Signal to noise ratio | ≥ 50 dB                                                                                                                                                                                                                                                                                      |
| Humanoid detection    | Support                                                                                                                                                                                                                                                                                      |
| Video processing      | PAL/NTSC video format is optional, supports automatic white balance, supports 3DNR,WDR,anti-face overexposure, and dehazing function, H.264/H.265/H.265+ different encoding formats are available, realize ultra-low storage, adjustable bit rate/frame rate.                                |
| Image Resolution      | Main stream: 3MP@25fps,1080P (default)/720P/D1@30fps,<br>Sub stream: D1/VGA/640*360/CIF@30fps,<br>Support CBR/VBR                                                                                                                                                                            |
| Network Interface     | One RJ45, 10/100M adaptive Ethernet interface 2KV lightning protection meter                                                                                                                                                                                                                 |
| Protocol support      | Support HTTP/RTSP/NTP/DHCP/ONVIF/P2P lamp network protocol, optional GB28181, RTMP and                                                                                                                                                                                                       |
| Intelligent functions | multiple private NVR protocols<br>IE6.0 and above (Web Server embedded in the device) browser use<br>Motion detection and OSD customization<br>Humanoid detection<br>IO alarm function<br>P2P cloud service<br>Support mobile web access<br>Support IP filtering<br>Active infrared function |
| Work Environment      | -30 °C~85 °C                                                                                                                                                                                                                                                                                 |

### Image reference Night vision:

